

Proximity Credential Order Form

CANSEC SYSTEMS LTD.

*** Must be completed and submitted with every credential order ***

Please complete the following form and fax it to 905-820-0301 or e-mail it to us at sales@cansec.com

1) Credential Type:

125kHz AWID-Compatible:

- 26-bit CanProx Branded Thin Proximity Card
- 37-bit CanProx Branded Thin Proximity Card
- 26-bit CanProx ISO-Thin Printable Proximity Card
- 37-bit CanProx ISO-Thin Printable Proximity Card
- 26-bit CanProx Proximity Key Tag
- 37-bit CanProx Proximity Key Tag
- 26-bit CanProx Proximity Patch
- 37-bit CanProx Proximity Patch
- 2-Button Smartfob RF Transmitter (315MHz) with 26-bit Proximity Coil
- 2-Button Smartfob RF Transmitter (315MHz) with 37-bit Proximity Coil
- 2-Button CanProx RF Transmitter (433MHz) with 26-bit Proximity Coil
- 2-Button CanProx RF Transmitter (433MHz) with 37-bit Proximity Coil
- 4-Button CanProx RF Transmitter (433MHz) with 26-bit Proximity Coil
- 4-Button CanProx RF Transmitter (433MHz) with 37-bit Proximity Coil

125kHz HID-Compatible:

- 26-bit CanProx CanProx Branded Thin Proximity Card
- 37-bit CanProx CanProx Branded Thin Proximity Card
- 26-bit CanProx ISO-Thin Printable Proximity Card
- 37-bit CanProx ISO-Thin Printable Proximity Card
- 26-bit CanProx Proximity Key Tag
- 37-bit CanProx Proximity Key Tag
- 26-bit CanProx Proximity Patch
- 37-bit CanProx Proximity Patch
- 2-Button Smartfob RF Transmitter (315MHz) with 26-bit Proximity Coil
- 2-Button Smartfob RF Transmitter (315MHz) with 37-bit Proximity Coil
- 2-Button CanProx RF Transmitter (433MHz) with 26-bit Proximity Coil
- 2-Button CanProx RF Transmitter (433MHz) with 37-bit Proximity Coil
- 4-Button CanProx RF Transmitter (433MHz) with 26-bit Proximity Coil
- 4-Button CanProx RF Transmitter (433MHz) with 37-bit Proximity Coil

125kHz HID:

- 26-bit HID ProxCard II
- 37-bit HID ProxCard II
- 26-bit HID ISOProx II Printable Graphics Card
- 37-bit HID ISOProx II Printable Graphics Card
- 26-bit HID ProxKey III Fob
- 37-bit HID ProxKey III Fob
- 26-bit HID MicroProx Tag
- 37-bit HID MicroProx Tag

13.56 MHz 2k bit HID iCLASS:

- 26-bit HID iCLASS SR Smart Card
- 37-bit HID iCLASS SR Smart Card
- 26-bit HID iCLASS SR Keytag
- 37-bit HID iCLASS SR Keytag
- 26-bit HID iCLASS SR Adhesive Patch
- 37-bit HID iCLASS SR Adhesive Patch

13.56 MHz 16k bit HID iCLASS:

- 26-bit HID iCLASS SR SmartCard
- 37-bit HID iCLASS SR SmartCard
- 26-bit HID iCLASS SR Keytag
- 37-bit HID iCLASS SR Keytag
- 26-bit HID iCLASS SR Stick-On Patch
- 37-bit HID iCLASS SR Stick-On Patch

2) For use with:

- SmartLock System (no Facility Code or Start ID required)
- Hurricane or Third Party System
Facility Code number: _____ Credential Start ID number: _____

3) Quantity: _____

4) Confirm Part Number as listed in Cansec Complete/SmartLock Price Book: _____

AUTHORIZED SIGNING OFFICER:

PRINT NAME

COMPANY NAME

SIGNATURE

DATE